



Enter & Exit Menus:



+



Print All Settings (in Menus):

Printer Control Emulation Mode EPSON FX

Font	Print Mode	Utility
Font	DRAFT Mode	HSD
Font	Pitch	10 CPI
Font	Proportional Spacing	No
Font	Style	Normal
Font	Size	Single

Symbol Sets	Character Set	Set I
Symbol Sets	Language Set	American
Symbol Sets	Zero Character	Slashed
Symbol Sets	Code Page	USA

Rear Feed	Line Spacing	6 LPI
Rear Feed	Form Tear-Off	500ms
Rear Feed	Skip Over Perforation	No
Rear Feed	Page Length	5.5 "

Bottom Feed	Line Spacing	6 LPI
Bottom Feed	Form Tear-Off	500ms
Bottom Feed	Skip Over Perforation	No
Bottom Feed	Page Length	5.5 "

Top Feed	Line Spacing	6 LPI
Top Feed	Bottom Margin	Valid
Top Feed	Page Length	5.5 "
Top Feed	Wait Time	1 sec
Top Feed	Page Length Control	by Actual Page Length

Set-Up	Graphics	Uni-directional
Set-Up	Receive Buffer Size	128 K
Set-Up	Paper Out Override	No
Set-Up	Print Registration	+1

||||| SET <- ||||| -> SHIFT+SET |||||

Set-Up	Operator Panel Function	Full Operation
Set-Up	Reset Inhibit	No
Set-Up	Print Suppress Effective	Yes
Set-Up	Auto LF	No
Set-Up	Time Out Print	Valid
Set-Up	Auto Select	Yes
Set-Up	Graphics Speed	Low
Set-Up	Centering Position	DEFAULT
Set-Up	Power Save Time	5 min
Set-Up	Time Out FF	Invalid

Parallel I/F	I-Prime	Buffer Print
Parallel I/F	Auto Feed XT	Invalid
Parallel I/F	Bi-Direction	Enable

Serial I/F	Parity	None
Serial I/F	Serial Data 7/8 Bits	8 Bits
Serial I/F	Protocol	Ready/Busy
Serial I/F	Diagnostic Test	No
Serial I/F	Busy Line	SSD-
Serial I/F	Baud Rate	9600 BPS
Serial I/F	DSR Signal	Invalid
Serial I/F	DTR Signal	Ready on Select
Serial I/F	Busy Time	200 ms